

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking**1.1. Product identifier**

Product name: Q5 AEROSOL

Product code: Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Lubricant / Lubricating oil. Use as a functional fluid.

1.3. Details of the supplier of the safety data sheet

Company name: Q Oil Europe Ltd,
Unit 2, Crown Point Ind Est Sth,
King Street,
Denton,
Manchester, M34 6HE
United Kingdom

Tel: +44 (0) 161 484 6505

Email: office@qoileurope.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 161 484 6505 (Office Hours Only)

Section 2: Hazards Identification**2.1. Classification of the substance or mixture**

Classification under CHIP: F+: R12

Classification under CLP: Flam. Aerosol 1: H222; -: EUH066

Most important adverse effects: Extremely flammable.

2.2. Label elements

Label elements under CLP:

Hazard statements: H222: Extremely flammable aerosol.

EUH066: Repeated exposure may cause skin dryness or cracking.

Signal words: Danger

Hazard pictograms: GHS02: Flame



Precautionary statements: P202: Do not handle until all safety precautions have been read and understood.

P281: Use personal protective equipment as required.

Section 2: Hazards Identification continued
2.2. Label elements cont'd

Precautionary statements: P302+350: IF ON SKIN: Gently wash with plenty of soap and water.
P211: Do not spray on an open flame or other ignition source.
P251: Pressurized container: Do not pierce or burn, even after use.
P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Label elements under CHIP:

Hazard symbols: H222: Extremely flammable aerosol.



Risk phrases: R12: Extremely flammable.

Safety phrases: S2: Keep out of the reach of children.
S29: Do not empty into drains.
S51: Use only in well-ventilated areas.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material.
Keep away from sources of ignition - No smoking.
Keep out of the reach of children.

Section 3: Composition/Information on Ingredients
3.2. Mixtures
Hazardous ingredients:

EINECS	CAS	CHIP Classification	CLP Classification	Percent
KEROSENE - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT				
265-149-8	64742-47-8	Xn: R65; N: R51/53	Asp. Tox. 1: H304	70-90%
PROPANE				
200-827-9	74-98-6	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
BUTANE				
203-448-7	106-97-8	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
4-HYDROXY-4-METHYLPENTAN-2-ONE				
204-626-7	123-42-2	Xi: R36	Eye Irrit. 2: H319	1-10%

Section 4: First Aid Measures

4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.
- Eye contact:** Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Remove any contact lenses and open eyes wide apart. Get medical attention if any discomfort continues
- Ingestion:** Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.
- Inhalation:** Remove from exposure, rest and keep warm. In severe cases, or if recovery is not rapid or complete, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** There may be mild irritation at the site of contact.
- Eye contact:** There may be irritation and redness.
- Ingestion:** There may be irritation of the throat.
- Inhalation:** There may be a feeling of tightness in the chest with shortness of breath. Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire Fighting Measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire fighters.

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental Release Measures
6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and Storage
7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Suitable packaging: Original container stored in a dry and cool place.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection
8.1. Control parameters
Hazardous ingredients:
Workplace exposure limits:
Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA 15 min.	STEL
PROPANE				
UK	1800 mg/m ³	7200 mg/m ³	-	-
BUTANE				
UK	1450 mg/m ³	1810 mg/m ³	-	-
4-HYDROXY-4-METHYLPENTAN-2-ONE				
UK	241 mg/m ³	362 mg/m ³	-	-

Section 8: Exposure controls/personal protection

8.2. Exposure controls

- Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.
- Respiratory protection:** Respiratory protection not required.
- Hand protection:** Impermeable gloves, change regularly to avoid permeation problems.
- Eye protection:** Safety glasses. Ensure eye bath is to hand.
- Skin protection:** Protective clothing.

Section 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

- State:** Aerosol
- Colour:** Colourless
- Odour:** Aromatic
- Evaporation rate:** Fast
- Oxidising:** Non-oxidising (by EC criteria)
- Solubility in water:** Slightly soluble
- Boiling point/range°C:** <=35
- Flash point°C:** <21
- Relative density:** 0.83 g/cm³

9.2. Other information

- Other information:** Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

- Reactivity:** Stable under recommended transport or storage conditions.

10.2. Chemical stability

- Chemical stability:** Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

- Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

- Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

Section 10: Stability and reactivity**10.5. Incompatible materials**

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: Acrid smoke and irritating fumes.

Section 11: Toxicological information**11.1. Information on toxicological effects**

Toxicity values: Not applicable.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath..

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information**12.1. Toxicity**

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations**13.1. Waste treatment methods**

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information**14.1. UN number**

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group**14.5. Environmental hazards**

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

Transport category: 2

Section 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.2. Chemical Safety Assessment**

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information**Other information**

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010. * indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H304: May be fatal if swallowed and enters airways.

H319: Causes serious eye irritation.

R12: Extremely flammable.

R36: Irritating to eyes.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.